

LONGLIFE complete



Sustainable development and production



EMAS:

- Continuous improvement of environmental performance
- Annual sustainability report
- Energy and water management
- Social Fairness



DIN ISO 14001:

- Continuous improvement in reducing waste and CO2 emissions, and saving of energy, water and material consumption



ISO 50001:

- Continuous improvement of energy management: performance, efficiency, security, use and consumption



A.I.S.E.-Charter:

- Safe and sustainable manufacturing of cleaning products



DIN ISO 9001:

- Continuous improvement of management processes and customer satisfaction
- Established quality management system in product development and production

green-Effective® Ultra-performance Floor Polish

■ Eco-efficient performance with eco-effective product design

User and environmental safety at the highest cleaning performance



- Developed to fulfil the Austrian Ecolabel
- Complete abandonment of toxic and harmful materials
- Outperforms other products at lower use concentration

Intensive use of renewable resources – continuous increase of the reutilisation score



- Production under extensive use of renewable raw materials and energy using to 100% hydroelectric, solar and geothermic power
- Active water stewardship maintaining an own fresh and waste water treatment

Ingredient declaration

For the ingredients list, please see the Safety Data Sheet

Traditional German quality - driving your durable business development



- More than 25 years pioneer in sustainable product development
- Smart hygiene solutions ensuring profitable growth
- Trusted brand

Professional user training and on-site support for Sustainable Hygiene Solutions



- Comprehensive knowledge transfer through qualified cleaning consultants
- Customized hygiene plans and cleaning recommendations optimizing your business and cleaning procedures
- Increased service value and strengthened company reputation





LOGLIFE complete



green-Effective® Ultra-performance Floor Polish

- Complete economy ■ Complete safety ■ Complete flexibility

Product profile

- LOGLIFE complete provides the complete solution for highest standards in coating of hard and elastic floors combined with exceptional environmental properties.
- Meanwhile enhancing the work safety, LOGLIFE complete assures outstanding durability and resistibility even against alcohol and skin disinfectants as well as a long-life pleasant appearance and gloss.
- LOGLIFE complete is completely user safe due to its time-saving processability even on damp linoleum floors, its reduced slip hazard whilst stripping and its easy-to-use features. Its certification according DIN 18032-2 proves outstanding slip resistance.
- LOGLIFE complete is as flexible as an elastic coating, extremely adhesive and elastic and therefore, suitable for elastomer (rubber) flooring and areas with high point load.
- This product works ideally in a system with LINAX complete, which easily removes even multi-layer LOGLIFE complete polymer films.
- By the complete abandonment of hazardous ingredients such as zinc, TBEP and fluorinated levelling agents, LOGLIFE complete takes on the responsibility for future generations.


Application and Dosing



Dose in relation to application. Follow below instructions.



Floor preparation: strip the floor, remove all dirt and old dispersion layers.



concentrated

Initial treatment: apply 2-3 thin and uniform layers. Drying time between the applications at least 30min.



Large areas: work in sections and apply wet in wet. Usage: approx. 2 L / 100 m².



200 mL/L

Coating refreshment: remove slight scratches using the spray-cleaner-method and a highspeed machine with red pad.

Area of application

- LOGLIFE complete is suitable for universal use on all coatable flooring especially elastic flooring made of PVC, linoleum, natural rubber and other special synthetic materials.
- Specially recommended for highly frequented areas, e.g. hospitals, schools, retail markets, airports, entrance areas etc. where high durability and long life cycle of coating is required.
- Not to be used on polished stone floors, stoneware tiles, as well as on unsealed wood.

Product safety, storage and environmental instructions

Safety: For professional use only. Keep away from children. Do not mix with other products. Test material compatibility before use. For further information, see Safety Data Sheet.

Storage: Store at room temperature in the original container. The storage and transport temperature of LOGLIFE complete must not exceed 30°C. Keep from freezing.

Environmental: Only give completely emptied packaging in the recommended waste container. Proper dosing saves costs and minimises environmental impact.

Sales units

Order No. 712513 2 x 5 L
Order No. 1112513 2 x 5 L

Your trusted partner on site

pH-Value

